



## Product Data Sheet

### PRODUCT DESCRIPTION

70805/7952 is a high solids chemical resistant, two-component, polyester aliphatic polyurethane designed for use as a topcoat over flooring & wall coating systems and as the primary wearing surface when applied to properly primed concrete.

70805/7952 combines superior resistance to chemical attack, ultra-violet degradation and excellent impact and abrasion resistance. U.S.D.A. acceptable.

### PRODUCT NUMBERS AND COLORS

Standard colors are: 70805-00 Clear  
70805-01 White  
70805-02 Gray  
70805-03 Tan  
70805-11 Light Gray

For special color consult NEOGARD®

### CURED FILM PERFORMANCE

Description	Test Method	Results
Tensile Strength	ASTM D412	4,000 psi
Elongation	ASTM D412	10%
Permanent Set	ASTM D412	<10%
Water Resistance	ASTM D471	<1%
MVT @ 5 mils	ASTM E96	1.4
Taber Abrasion	ASTM D4060	40 mg/1,000 cs-17
Adhesion	ASTM D4541	300 psi
Flammability	ASTM D635	Pass

The above tested results are typical values. Individual lots may vary up to 10% from the typical value.

### PRODUCT DATA

Description	Test Method	Results
Weight/Gal (mixed)	ASTM D1475	8.63 lbs/gal
Weight Solids (mixed)	ASTM D4209	62%
Volume Solids (mixed)	Calculated	58%
VOC (mixed)	EPA Method 24	335 g/L
Viscosity (mixed)	ASTM D2196	400 cps
Flash Point	ASTM D3278	102°F

The above tested results are typical values. Individual lots may vary up to 10% from the typical value.

### APPLICATIONS

70805/7952 is used as a topcoat and corrosion resistant wearing surface on a variety of prepared substrates.

- Over epoxy primed concrete.
- Over trowelled resinous flooring.
- Over decorative floor systems.
- Over self-leveling systems.
- Can be used interior and exterior.
- Over WallGard high build wall systems.

For surface preparation and application instruction, refer to NEOGARD's Flooring Systems Manual for specific applications.

### HEALTH AND SAFETY

Read the Material Safety Data Sheet (MSDS) and container labels for detailed health and safety information. This product is intended for industrial use by properly trained professional applicators only.

The information, data and suggestions contained herein are believed to be reliable, based upon our knowledge and experience; however, it is expressly declared that Seller does not guarantee the result to be obtained in Buyer's process. **SELLER HEREBY EXPRESSLY DISCLAIMS ANY IMPLIED WARRANTY OF MERCHANTABILITY FOR FITNESS FOR A PARTICULAR PURPOSE AND/OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED** as to any and all products and/or suggestions described herein, whether such products are used alone or in combination with other materials. Buyer must make its own determination of the suitability of any product for its use, and the completeness of any information contained herein. Nothing contained herein shall be construed to constitute inducement or recommendation to practice any invention covered by any patent without authority from the owner of the patent. Applicator is an independent contractor of, and should under no circumstances be viewed as an employee or agent of, the NEOGARD® Division of JONES-BLAIR®. 05212010/70805/7952PD.indd

**NEOGARD®**

Div. of JONES-BLAIR®

2728 Empire Central - Dallas, Texas 75235 - Toll Free (800) 321-6588 - Fax (214) 357-7532 - www.neogard.com