



Product Data Sheet

PRODUCT DESCRIPTION

7125 Water-Borne Acrylic Sealer is a single component clear topcoat designed to seal WalkTrak pedestrian traffic coating systems where heavier foot traffic, stain or dirt resistance is required.

PRODUCT NUMBER AND COLOR

7125 - Milky white, dries clear

PRODUCT DATA

Description	Test Method	Results
Weight/Gal	ASTM D1475	8.54 lbs/gal
Weight Solids	ASTM D4209	24.8%
Volume Solids	Calculated	22%
VOC	EPA Method 24	184 g/L
Viscosity	ASTM D562	15 seconds, Zahn 2
Flash Point	ASTM D3278	None
Dry Time @ 77°F, 50% RH		To Touch: 30 minutes To Recoat: 1 hour
Adhesion to Concrete	ASTM D4541	300 psi

The above are typical values. Individual lots may vary up to 10% from the typical values.

SURFACE PREPARATION

WalkTrak surfaces must be clean, fully dried and cured before application of 7125.

DIRECTIONS FOR USE

THINNING: Not required. Use as is.

APPLICATION: Apply at the rate of 200 - 400 square feet per gallon. May be brushed, rolled or sprayed. **DO NOT APPLY WHEN TEMPERATURE CONDITION IS BELOW 45°F.**

CLEAN-UP: Clean-up skin, clothing, paint tools or spills immediately with warm soapy water.

STORAGE

Unopened containers of sealer material should be stored in a cool (75°F) area. Do not store below 35°F.

AVOID FREEZING!

HEALTH AND SAFETY

Before using this product, carefully read the Material Safety Data Sheet (MSDS) and container labels for detailed health and safety information. This product is intended for industrial use by properly trained professional applicators only.

The information, data and suggestions contained herein are believed to be reliable, based upon our knowledge and experience; however, it is expressly declared that Seller does not guarantee the result to be obtained in Buyer's process. **SELLER HEREBY EXPRESSLY DISCLAIMS ANY IMPLIED WARRANTY OF MERCHANTABILITY FOR FITNESS FOR A PARTICULAR PURPOSE AND/OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED** as to any and all products and/or suggestions described herein, whether such products are used alone or in combination with other materials. Buyer must make its own determination of the suitability of any product for its use, and the completeness of any information contained herein. Nothing contained herein shall be construed to constitute inducement or recommendation to practice any invention covered by any patent without authority from the owner of the patent. Applicator is an independent contractor of, and should under no circumstances be viewed as an employee or agent of, the NEOGARD® Division of JONES-BLAIR®. 02202008/7125PD.indd

NEOGARD®
Div. of JONES-BLAIR®

2728 Empire Central - P.O. Box 35286 - Dallas, Texas 75235 - Toll Free (800) 321-6588 - Fax (214) 357-7532 - www.neogard.com