



Product Data Sheet

PRODUCT DESCRIPTION

7790 is a water reducible urethane primer for use on wood and concrete surfaces prior to application of surface applied waterproofing systems. Mix one part 7790 with one part water by volume.

PRODUCT NUMBERS AND COLORS

Standard color is: Amber

CURED FILM PERFORMANCE

Description	Test Method	Results
Adhesion	ASTM D4541	500 psi

The above tested result is a typical value. Individual lots may vary up to 10% from the typical value.

PRODUCT DATA

Description	Test Method	Results
Weight/Gal (mixed)	ASTM D1475	9.24 lb/gal
Weight Solids (mixed)	Calculated	53
Volume Solids (mixed)	Calculated	50
VOC (mixed)	EPA Method 24	0 g/L
Viscosity (mixed)	ASTM D2196	<50 cps
Flash Point	ASTM D3278	>230°F

The above tested results are typical values. Individual lots may vary up to 10% from the typical value.

HANDLING AND SAFETY

7790 contains reactive isocyanate groups. Use with adequate ventilation to keep airborne isocyanate level below TLV of 0.005 ppm TWA (ACGIH) and 0.02 PEL ceiling (OSHA).

DO NOT BREATHE VAPOR OR SPRAY MIST. Wear an appropriate, properly fitted respirator (NIOSH approved) during application unless air monitoring demonstrates vapor/mist levels are below applicable limits. An airline respirator (NIOSH approved) is recommended. A vapor/

particulate respirator (NIOSH approved) may be appropriate where airborne monitoring demonstrates vapor levels below ten times the applicable exposure limits. Follow respirator manufacturer's directions for respirator use.

INDIVIDUALS WITH LUNG OR BREATHING PROBLEMS OR PRIOR REACTION TO ISOCYANATES MUST NOT BE EXPOSED TO VAPORS, SPRAY MIST, OR ALLOWED IN AREA UNTIL COATING HAS DRIED AND AREA IS FREE OF ALL VAPORS.

Avoid contact with eyes, skin, and clothing. Wear chemical splash goggles, rubber gloves, and other equipment as appropriate for protection. Do not ingest.

Do not smoke or weld during application. No open flames or heat sources should be near vapors or spray mists. Vapor, spray mist and thermal decomposition products are harmful. These can cause eye, skin, or respiratory tract irritation and allergic skin reaction.

FIRST AID: A person affected by inhalation of vapor or spray mist should be removed to fresh air. If breathing difficulty persists or occurs later, call a physician and have label information available. In case of eye contact, flush immediately with plenty of water and for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water. If material is swallowed do not induce vomiting. **CALL A PHYSICIAN IMMEDIATELY.**

See Material Safety Data Sheet (MSDS) for specific product analysis, the threshold limit value (TLV) and detailed handling and application instructions.

STORAGE

7790 has a shelf life of 12 months from the date of manufacture. Should freezing occur, the material must be thawed thoroughly and mixed until uniform. **KEEP CONTAINER CLOSED WHEN NOT IN USE.** Do not transfer contents to other storage containers. In case of spillage, absorb and then dispose of in accordance with applicable regulations.

Special Instructions for previous coated surfaces:

7790: 4 parts

Water: 1 part

Acetone: 3 parts

Mix the above and apply quickly.

Manufacturer warrants that the standards and qualities of the product described herein will not vary by more than 10% from the tested results set forth above. **MANUFACTURER HEREBY EXPRESSLY DISCLAIMS ANY AND ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, WITHOUT LIMITATION, ANY IMPLIED WARRANTY OF MERCHANTABILITY AND/OR IMPLIED WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE.** Buyer must make its own determination of the suitability of any product for its use, whether such product is used alone or in combination with other materials. **To the extent this or any of Manufacturer's products is proven to be defective, Buyer's sole remedy shall be limited to the replacement of such defective product, exclusive of any costs of labor. MANUFACTURER SHALL NOT BE LIABLE OR OBLIGATED FOR ANY LOSS OR CONSEQUENTIAL OR OTHER DAMAGE INCURRED DIRECTLY OR INDIRECTLY BY BUYER OR ANY OTHER PERSON OR ENTITY THAT ARISES IN ANY WAY IN RELATION TO THIS OR ANY OF MANUFACTURER'S OTHER PRODUCTS.** Nothing contained herein shall be construed to constitute inducement or recommendation to practice any invention covered by any patent without authority of the owner of the patent. No Applicator is or should be viewed as an employee or agent of Manufacturer. 10262010/7790PD.indd

NEOGARD Div. of JONES-BLAIR

2728 Empire Central - Dallas, Texas 75235 - Phone (214) 353-1600 - Fax (214) 357-7532 - www.neogard.com