

# 86218 (ETERNABOND™ WebSeal™)

Product Data Sheet

Flashing Tape

## BASIC USE

Eternabond WebSeal Tape is used to seal roof joints (seams) and tears, flashings, copings, skylights, gutters, etc. Perfect for repairing and restoring roofs on mobile homes and RVs. Extremely flexible, with no memory, so WebSeal conforms to virtually any shape without springing back. WebSeal also seals to itself so it can be cut and folded around an object, as if wrapping a present.

WebSeal permanently bonds to a wide range of surfaces including difficult roof materials such as EPDM, TPO, CSPE/Hypalon, most PVC, CPE, SBS, APP modifies, asphalt BURs, coal tar BURs, plus all metal roofs, tiles, shingle, aluminum, Galvanized steel, gypsum board, wood, polyethylene, propylene, polystyrene, fiberglass, brick, concrete, masonry, OSB, etc.

## COMPOSITION

Eternabond WebSeal utilizes EternaBond's advanced MicroSealant™ Technology, a 100% solids formulation of synthetic resins, thermoplastics and non-curing rubber (non butyl) with a built in primer, bonded to a woven polyester backing for maximum conformability. Designed not to harden under even the most rigorous conditions. Sag temp > 200°F. Adhesive is protected (while in a roll) by a tough, easily removed siliconized polymer release liner, which prevents contamination prior to its use. All materials are prefabricated to provide uniform thickness.

## TECHNICAL DATA

Description	Results
Standard roll size	NEOGARD stocks 6" X 50'
Standard case quantity	100 sq. ft. per case
Available widths	Up to 48"
Total Thickness	30 mils (1 mm)
Adhesion	19 lbs/in width
Low temp flexibility	Excellent
Temperature range	-70°F - >200°F
Pliability	No cracks in membrane
Water vapor test (ASTM E96B)	.005 grms/100" sq./24hrs/100°F
Permanence	.001 perms maximum
Elongation	>500%
Application temp	>150°F to -20°F (with EternaPrime)
Shelf life	Up to 5 years

## SURFACE PREPARATION

Surface must be clean and dry; free of loose rust and scale, dust, talc, and dirt. Oil, grease, and other contaminants should be removed with a suitable solvent/cleaner. Use of EternaPrime reduces clean up. For older plastic roofs, score surface with sand cloth and wipe away dust.

## APPLICATION

Install Eternabond WebSeal over the repair area, removing the siliconized plastic release liner gradually to prevent contamination of the adhesive prior to application. Rub or roll with pressure with hand or steel roller to activate bonding process. This material may be applied to clean dry surfaces from 150°F+ to -20°F. Treat surface with EternaPrime for installations from 40°F to -20°F. A topcoat of roof coating is necessary for UV protection.

For additional information on ETERNABOND WebSeal, please visit their website at:

**ETERNABOND**

ETERNABOND, Inc.

Hawthorn Woods, IL

Phone: (888) 336-2663

Fax: (847) 540-7413

www.eternabond.com

The information, data and suggestions contained herein are believed to be reliable, based upon our knowledge and experience; however, it is expressly declared that Seller does not guarantee the result to be obtained in Buyer's process. **SELLER HEREBY EXPRESSLY DISCLAIMS ANY IMPLIED WARRANTY OF MERCHANTABILITY FOR FITNESS FOR A PARTICULAR PURPOSE AND/OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED** as to any and all products and/or suggestions described herein, whether such products are used alone or in combination with other materials. Buyer must make its own determination of the suitability of any product for its use, and the completeness of any information contained herein. Nothing contained herein shall be construed to constitute inducement or recommendation to practice any invention covered by any patent without authority from the owner of the patent. Applicator is an independent contractor of, and should under no circumstances be viewed as an employee or agent of, the NEOGARD® Division of JONES-BLAIR®. 013007-86218PD.indd

**NEOGARD®**

Div. of JONES-BLAIR®

2728 Empire Central - P.O. Box 35286 - Dallas, Texas 75235 - Toll Free (800) 321-6588 - Fax (214) 357-7532 - www.neogard.com

